

Monomeric transparent gloss laminate featuring a permanent acrylic based adhesive. This material has been specifically designed for protecting digital prints.

IP 2820-101

Monomeric film featuring specific polymeric, non-migrating plasticizers and UV stabilizers, which ensure maximum light fastness and good outdoor durability. IP 2820-101 is intended for many flat applications, both interior and exterior, such as markings & decorations, window and vehicle graphics.

This laminate can be used on IP 2511, IP 2512, IP 2513 and IP 2514. It can also be used on many other speciality materials such as IP 2901FR, IP 2903, IP 2905, IP 2906, IP 2909 and IP 2910.

Specifications	
DESCRIPTION	Monomeric laminate
COLOUR	Transparent gloss
FACE FILM THICKNESS	80 μ
WEIGHT	N/A
ADHESIVE	Acrylic permanent
ADHESIVE STRENGTH	16N / 25mm (Finat TM 1/24h)
RELEASE PAPER	PE-coated silicone paper, 140g / m ²
TEMPERATURE RANGE	-40°C to +80°C
DURABILITY (UNPRINTED)	Up to 3 years
FLAME RETARDANCY	Adhered to steel, self-extinguishing
SHELF LIFE	2 years, 20°C / 50% humidity
RECOMMENDATION	For optimum quality, please ensure that the media feed adjustment has been completed for this material

© November 2007 Spandex Group. Technical specifications subject to change without prior notice.
All trademarks mentioned are property of their respective owners. Output may vary depending on the type of print data/file, application, media, environmental conditions, print speed, or other variables.